

**Material Safety Data Sheet**  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U.S. Department of Labor**  
**Occupational Safety and Health Administration**  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072



**IDENTITY** (As Used on Label and List)

TENSIVE® CONDUCTIVE ADHESIVE GEL

*Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

**Section I**

**Manufacturer's Name**

PARKER LABORATORIES, INC.

**Address (Number, Street, City, State and ZIP Code)**

286 ELDRIDGE ROAD

FAIRFIELD, NJ 07004

**Emergency Telephone Number**

**Telephone Number for Information**

(973) 276-9500

**Date Prepared**

AUGUST 2012

**Signature of Preparer (optional)**

**Section II – Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
NONE				

**Section III – Physical/Chemical Characteristics**

<b>Boiling Point</b>	N/A	<b>Specific Gravity (H<sup>2</sup>O = 1)</b>	1.0
<b>Vapor Pressure (mm Hg.)</b>	N/A	<b>Melting Point</b>	N/A
<b>Vapor Density (AIR = 1)</b>	N/A	<b>Evaporation Rate (Butyl Acetate = 1)</b>	N/A
<b>Solubility in Water</b>	SOLUBLE		

**Appearance and Odor**  
 VISCOUS, AMBER COLORED GEL; PERFUMED ODOR

**Section IV – Fire and Explosion Hazard Data**

<b>Flash Point (Method Used)</b> N/A	<b>Flammable Limits</b> N/A	<b>LEL</b> N/A	<b>UEL</b> N/A
<b>Extinguishing Media</b> USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.			
<b>Special Fire Fighting Procedures</b> NONE			

**Unusual Fire and Explosion Hazards**  
 NONE

